

# Product Environmental Profile

ETIKA™

2P+E socket outlet German standard 16A



## LEGRAND'S ENVIRONMENTAL COMMITMENTS

### • Incorporate environmental management into our industrial sites

Of all Legrand sites worldwide, over 85% are ISO 14001-certified (sites belonging to the Group for more than five years).

### • Offer our customers environmentally friendly solutions

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.



### • Involve the environment in product design and provide informations in compliance with ISO 14025

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



## REFERENCE PRODUCT

<b>Function</b>	Connect/Disconnect during 20 years the plug of a load consuming 16A under a voltage of 250V while protecting the user from direct contact with live parts.	
<b>Reference Product</b>		
	Cat.No 6 722 21 2P+E socket outlet	Cat.No 6 725 01 Plate 1gang white
	2P+E socket outlet german standard screw terminal with shutter 16A 250 V- White	

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.



## PRODUCTS CONCERNED

The environmental data is representative of the following products:

Catalogue Numbers						
mechanisms without shutter	mechanisms with shutter	1 gang plate	2 gang plate	3 gang plate	4 gang plate	5 gang plate
• 6 722 21	• 6 722 22	• 6 725 01	• 6 725 02	• 6 725 03	• 6 725 04	• 6 725 05
• 6 723 21	• 6 723 22	• 6 725 11	• 6 725 12	• 6 725 13	• 6 725 14	• 6 725 15
• 6 724 21	• 6 724 22	• 6 725 81	• 6 725 82	• 6 725 83	• 6 725 84	• 6 725 85
• 6 726 21	• 6 726 22	• 6 725 51	• 6 725 52	• 6 725 53	• 6 725 54	• 6 725 55

# Product Environmental Profile

ETIKA™

2P+E socket outlet German standard 16A



## ■ CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It respects the restrictions on use of hazardous substances as defined in the RoHS directive 2011/65/EU amended by delegated directive (EU) 2015/863, and its amendment 2017/2102/EU.

<b>Total weight of Reference Product</b>		<b>108 g</b> (all packaging included)			
<b>Plastics as % of weight</b>		<b>Metals as % of weight</b>		<b>Other as % of weight</b>	
PC	27.0 %	Steel	9.3 %		
ABC	11.0 %	Copper alloys	7.7 %		
PS	<0.1 %				
<b>Packaging as % of weight</b>					
PP	4.5 %			Wood	23.3 %
PE	0.1 %			Paper	17.1 %
<b>Total plastics</b>	<b>42.6 %</b>	<b>Total metals</b>	<b>17.0 %</b>	<b>Total others</b>	<b>40.4 %</b>

Estimated recycled material content: 20 % by mass.



## ■ MANUFACTURE

This Reference Product comes from a site that has received ISO14001 certification.



## ■ DISTRIBUTION

Products are distributed from logistics centres located with a view to optimize transport efficiency.

The Reference Product is therefore transported over an average distance of 297 km by road from our warehouse to the local point of distribution into the market in Russia.

Packaging is compliant with applicable regulation. At their end of life, its recyclability rate is 87% (in % of packaging weight).



## ■ INSTALLATION

For the installation of the product, only standard tools are needed.



## ■ USE

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.

# Product Environmental Profile

ETIKA™

2P+E socket outlet German standard 16A



## END OF LIFE

The product end of life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse.

### • Recyclability rate:

Calculated using the method described in technical report IEC/TR 62635, the recyclability rate of the product is estimated at 92%. This value is based on data collected from a technological channel operating on an industrial basis. It does not pre-validate the effective use of this channel for end of life of this product.

Separated into:

- plastic materials (excluding packaging): 36 %
- metal materials (excluding packaging): 17 %
- packaging (all types of materials): 39 %



## ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle : manufacturing, distribution, installation, use and end of life.

It is representative from products marketed and used in Russia.

For each phase, the following modelling elements were taken in account :

<b>Manufacture</b>	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing.
<b>Distribution</b>	Transport between the last Group distribution centre and an average delivery point in the sales area.
<b>Installation</b>	The end of life of the packaging.
<b>Use</b>	<ul style="list-style-type: none"> <li>• Product category: PSR-0005-ed2-EN-2016 03 29 - § 3.8.1.1 - Power socket and electronic connection socket.</li> <li>• Use scenario : non-continuous operation for 20 years at 50% of rated load, during 50% of the time. This modelling duration does not constitute a minimum durability requirement.</li> <li>• Energy model : Electricity Mix; Russia, year 2009.</li> </ul>
<b>End of Life</b>	The default end of life scenario maximizing the environmental impacts.
<b>Software and database used</b>	EIME & database CODDE-2018-11

# Product Environmental Profile

ETIKA™

2P+E socket outlet German standard 16A



## SELECTION OF ENVIRONMENTAL IMPACTS

	Total for Life cycle		Raw material and manufacture		Distribution		Installation		Use		End of life	
Global warming	6.23E+00	kgCO <sub>2</sub> eq.	4.10E-01	7 %	1.59E-03	< 1 %	2.98E-03	< 1 %	5.81E+00	93 %	6.08E-03	< 1 %
Ozone depletion	1.77E-07	kgCFC-11 eq.	2.46E-08	14 %	3.23E-12	< 1 %	2.55E-11	< 1 %	1.53E-07	86 %	1.33E-10	< 1 %
Acidification of soils and water	4.97E-03	kgSO <sub>2</sub> eq.	8.13E-04	16 %	7.17E-06	< 1 %	1.35E-05	< 1 %	4.11E-03	83 %	2.36E-05	< 1 %
Water eutrophication	2.69E-03	kg(PO <sub>4</sub> ) <sup>3-</sup> eq.	1.57E-03	58 %	1.65E-06	< 1 %	9.91E-06	< 1 %	1.08E-03	40 %	2.96E-05	1 %
Photochemical ozone formation	1.20E-03	kgC <sub>2</sub> H <sub>4</sub> eq.	8.08E-05	7 %	5.09E-07	< 1 %	9.70E-07	< 1 %	1.12E-03	93 %	1.83E-06	< 1 %
Depletion of abiotic resources - elements	2.76E-05	kgSb eq.	2.75E-05	100 %	6.38E-11	< 1 %	1.38E-10	< 1 %	5.96E-08	< 1 %	3.65E-10	< 1 %
Total use of primary energy	5.74E+01	MJ	8.64E+00	15 %	2.26E-02	< 1 %	3.98E-02	< 1 %	4.86E+01	85 %	6.82E-02	< 1 %
Net use of fresh water	3.35E-02	m <sup>3</sup>	2.75E-02	82 %	1.43E-07	< 1 %	9.92E-07	< 1 %	6.02E-03	18 %	4.62E-06	< 1 %
Depletion of abiotic resources - fossil fuels	4.37E+01	MJ	5.28E+00	12 %	2.24E-02	< 1 %	3.85E-02	< 1 %	3.83E+01	88 %	6.21E-02	< 1 %
Water pollution	2.77E+02	m <sup>3</sup>	1.10E+02	40 %	2.62E-01	< 1 %	4.49E-01	< 1 %	1.66E+02	60 %	7.21E-01	< 1 %
Air pollution	4.03E+02	m <sup>3</sup>	1.03E+02	25 %	6.54E-02	< 1 %	2.66E-01	< 1 %	3.00E+02	74 %	6.48E-01	< 1 %

The values of the 27 impacts defined in the PCR-ed3-EN-2015 04 02 are available in the digital database of pep-ecopassport.org website.

The environmental impacts are calculated for a configuration composed by a socket-outlet and a plate. For products covered by the PEP other than the Reference Product, to obtain the environmental impacts of each phase of the lifecycle:

- for the configurations with different cover and plate finishing, take the same values of those of the Reference Product,
- for the configurations with shutters, apply a coefficient 8 on the indicator Ozon Depletion for the Manufacturing phase only,
- for the multi-gang configuration, the full environmental impacts of the Reference Product have to be multiplied by the number of installed products.

Registration number: LGRP-01294-V01.01-EN	Drafting rules: PEP-PCR-ed3-EN-2015 04 02 Supplemented by PSR-0005-ed2-2016 03 29
Verifier accreditation N°: VH23	Information and reference documents: <a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
Date of issue: 01/2022	Validity period: 5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2010 Internal <input checked="" type="checkbox"/> External <input type="checkbox"/>	
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)	
PEP are compliant with XP C08-100-1 : 2016 The elements of the present PEP cannot be compared with elements from another program	
Document in compliance with ISO 14025 : 2010: «Environmental labels and declarations. Type III environmental declarations»	
Environmental data in alignment with EN 15804: 2012 + A1 : 2013	

