

Product Environmental Profile

**2 core to 24 core 10G (50/125) OM3
indoor Multimode fiber optic cable PVC**



LEGRAND'S ENVIRONMENTAL COMMITMENTS

• Incorporate environmental management into our industrial sites

Of all Legrand sites worldwide, over 85% are ISO 14001-certified (sites belonging to the Group for more than five years).

• Offer our customers environmentally friendly solutions

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.


• Involve the environment in product design and provide informations in compliance with ISO 14025

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



REFERENCE PRODUCT

Function	<p>Transmit a communication signal on 1 m according to TIA-568-C.3-2009 for indoor Multimode 24 core (OM3) fiber during a 10 year typical lifetime.</p> <p>Lifetime and use rate match the Building - LAN : Commercial application defined in the table given in annex 1 of the wires, cables and accessories specific rules.</p>
Reference Product	 <p>Cat.No 3251324C</p> <p>24 core 10G(50/125) OM3 indoor Multimode fiber optic cable PVC.</p>

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.



PRODUCTS CONCERNED

The environmental data is representative of the following products:

Catalogue Numbers
<ul style="list-style-type: none"> • 2 core: 3251302C • 4 core: 3251304C • 6 core: 3251306C • 8 core: 3251308C • 24 core: 3251324C

Product Environmental Profile

2 core to 24 core 10G (50/125) OM3
indoor Multimode fiber optic cable PVC



■ CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It respects the restrictions on use of hazardous substances as defined in the RoHS directive 2011/65/EU amended by delegated directive (EU) 2015/863, and its amendment 2017/2102/EU.

Total weight of Reference Product		213 g (all packaging included)			
Plastics as % of weight		Metals as % of weight		Other as % of weight	
PVC	58.3 %			Glass	4.6 %
PA	4.2 %				
PET	0.6 %				
Packaging as % of weight					
		Steel	1.8 %	Wood	30.5 %
Total plastics	63.1 %	Total metals	1.8 %	Total others	35.1 %

Estimated recycled material content: 20 % by mass.



■ MANUFACTURE

This Reference Product comes from a site that have received ISO14001 certification.



■ DISTRIBUTION

Products are distributed from logistics centres located with a view to optimize transport efficiency. The Reference Product is therefore transported over an average distance of 850 km by road from our warehouse to the local point of distribution into the market in China.

Packaging is compliant with applicable regulation. At their end of life, its recyclability rate is 95 % (in % of packaging weight).



■ INSTALLATION

For the installation of the product, only standard tools are needed.



■ USE

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.

Product Environmental Profile

2 core to 24 core 10G (50/125) OM3
indoor Multimode fiber optic cable PVC



END OF LIFE

The product end of life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse.

• Recyclability rate:

Calculated using the method described in technical report IEC/TR 62635, the recyclability rate of the product is estimated at 94 %. This value is based on data collected from a technological channel operating on an industrial basis. It does not pre-validate the effective use of this channel for the end of life of this product.

Separated into:

- plastic materials (excluding packaging) : 60 %
- other materials (excluding packaging) : 5 %
- packaging (all types of materials) : 29 %



ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use and end of life. It is representative of products marketed and used in China.

For each phase, the following modelling elements were taken in account:

Manufacture	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing.
Distribution	Transport between the last Group distribution centre and an average delivery point in the sales area.
Installation	The end of life of the packaging.
Use	<ul style="list-style-type: none"> • Product category: § 4 «Communication and data wires and cables» § 4.2.2.3 «optical fiber cables». • Use scenario: non-continuous operation for 10 years of working life, during 25% of the time (for LAN tertiary applications), 18.24mW of energy losses (determined by standard TIA-568-C.3-2009 for fiber). This modelling duration does not constitute a minimum durability requirement. • Energy model: Electricity Mix; China - 2009.
End of life	The default end of life scenario maximizing the impacts.
Software and database used	EIME & database CODDE-2018-11

Product Environmental Profile

2 core to 24 core 10G (50/125) OM3
indoor Multimode fiber optic cable PVC



SELECTION OF ENVIRONMENTAL IMPACTS

	Total for Life cycle		Raw material and manufacture		Distribution		Installation		Use		End of life	
Global warming	7,36E-01	kgCO ₂ eq.	5,84E-01	79 %	9,02E-03	1 %	3,24E-03	< 1 %	4,06E-04	< 1 %	1,39E-01	19%
Ozone depletion	1,27E-07	kgCFC-11 eq.	1,21E-07	96 %	1,83E-11	< 1 %	6,57E-12	< 1 %	3,23E-12	< 1 %	5,33E-09	4%
Acidification of soils and water	1,28E-03	kgSO ₂ eq.	1,10E-03	86 %	4,05E-05	3 %	1,46E-05	1 %	4,40E-07	< 1 %	1,30E-04	10%
Water eutrophication	4,62E-04	kg[PO ₄] ³⁻ eq.	3,46E-04	75 %	9,31E-06	2 %	3,35E-06	< 1 %	1,16E-07	< 1 %	1,03E-04	22%
Photochemical ozone formation	1,18E-04	kgC ₂ H ₄ eq.	1,01E-04	86 %	2,88E-06	2 %	1,04E-06	< 1 %	5,20E-08	< 1 %	1,26E-05	11%
Depletion of abiotic resources - elements	6,22E-08	kgSb eq.	5,82E-08	94 %	3,61E-10	< 1 %	1,30E-10	< 1 %	1,78E-12	< 1 %	3,51E-09	6%
Total use of primary energy	9,68E+00	MJ	8,77E+00	91 %	1,28E-01	1 %	4,59E-02	< 1 %	6,65E-03	< 1 %	7,30E-01	8%
Net use of fresh water	1,46E-02	m ³	1,44E-02	99 %	8,07E-07	< 1 %	2,90E-07	< 1 %	4,53E-07	< 1 %	1,29E-04	< 1%
Depletion of abiotic resources - fossil fuels	3,75E+00	MJ	3,12E+00	83 %	1,27E-01	3 %	4,56E-02	1 %	6,14E-03	< 1 %	4,49E-01	12%
Water pollution	2,54E+02	m ³	1,04E+02	41 %	1,48E+00	< 1 %	5,34E-01	< 1 %	2,02E-02	< 1 %	1,47E+02	58%
Air pollution	5,40E+01	m ³	4,86E+01	90 %	3,70E-01	< 1 %	1,33E-01	< 1 %	4,21E-02	< 1 %	4,89E+00	9%

The values of the 27 impacts defined in the PCR-ed3-EN-2015 04 02 are available in the digital database of pep-ecopassport.org website.

Product Environmental Profile

2 core to 24 core 10G (50/125) OM3
indoor Multimode fiber optic cable PVC



SELECTION OF ENVIRONMENTAL IMPACTS

For the products in 2, 4, 6 and 8 core configurations the environmental impacts of each phase of the lifecycle are obtained by adopting the following coefficients.

		SUM		Manufacturing		Distribution		Installation		Use		End of life	
		8 core	6 core	8 core	6 core	8 core	6 core	8 core	6 core	8 core	6 core	8 core	6 core
Global warming	GWP	0.2	0.2	0.2	0.2	0.2	0.2	0.1	0.3	0.3	0.3	0.2	0.2
Ozon depletion	ODP												
Acidification of soil and water	A												
Water eutrophication	EP												
Photochemical ozone creation	POCP												
Depletion of abiotic resources - elements	ADPe												
Total use of primary energy during the life cycle	PE												
Net use of fresh water	FW												
Depletion of abiotic resources - fossil fuels	ADPf												
Water pollution	WP												
Air pollution	AP												

		SUM		Manufacturing		Distribution		Installation		Use		End of life	
		4 core	2 core	4 core	2 core	4 core	2 core	4 core	2 core	4 core	2 core	4 core	2 core
Global warming	GWP	0.2	0.1	0.2	0.1	0.2	0.1	0.3	0.2	0.3	0.1	0.1	0.1
Ozon depletion	ODP												
Acidification of soil and water	A												
Water eutrophication	EP												
Photochemical ozone creation	POCP												
Depletion of abiotic resources - elements	ADPe												
Total use of primary energy during the life cycle	PE												
Net use of fresh water	FW												
Depletion of abiotic resources - fossil fuels	ADPf												
Water pollution	WP												
Air pollution	AP												

Registration number: LGRP-01158-V01.01-EN	Drafting rules: «PEP-PCR-ed3-EN-2015 04 02» Supplemented by PSR-0001-ed3-2015 10 16
Verifier accreditation N°: VH02	Information and reference documents: www.pep-ecopassport.org
Date of issue: 10-2020	Validity period: 5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2010 Internal <input checked="" type="checkbox"/> External <input type="checkbox"/>	
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)	
PEP are compliant with XP C08-100-1 : 2016 The elements of the present PEP cannot be compared with elements from another program	
Document in compliance with ISO 14025 : 2010: «Environmental labels and declarations. Type III environmental declarations»	
Environmental data in alignment with EN 15804: 2012 + A1 : 2013	

